

# Wall Decal Care Sheet

**Please Read Carefully!**

**ONLY apply this wall decal to GLOSS OR SEMI-GLOSS LATEX PAINTED WALLS**

**IF UNSURE (FOR ANY REASON) OF WHAT KIND OF PAINT IS ON YOUR WALL-\*DO NOT MOUNT!**

**\*See Optional Mounting Idea Below**

**Paint MUST be painted 30+ days PREVIOUSLY.**

1: Unroll and lay flat for 24 hrs. before application.

## **LOTION-FREE HANDS!!**

2: Apply decal straight down with both hands. If decal is large 2 people will be helpful. From middle outward, smooth decal with hands pushing air out from middle. Roll up a hand towel tightly and smooth from middle outward again. If any bubbles remain, gently pin prick to side of trapped air and push outward with finger.

3: Window application acceptable (Gymnasiums). Ideal temperature 50 Degrees or higher. Do not clean with ammonia cleaning products.

**Optional Mounting Idea: Purchase "Bath Board" at your local Lowe's or Home Depot. This is used to line shower walls. It is already painted smooth and is recommended for wall decals. You can usually get it cut to size while you wait. You can move your decal from wall to wall and keep FOREVER!**

**Car Decals:** **Vehicle Mounting:** Thoroughly clean and completely remove wax! Completely dry and wipe with rubbing alcohol. Let dry. Align decal to level. Tape on opposite sides to position helpful. Gently pull decal away from liner 1/2 way down decal. Cut off backing paper. Smooth decal from middle outward with a credit-type card for a squeegee. Lift remaining decal up to release remaining backing paper. Smooth decal from middle down and outward. Roll a hand towel up tightly. Smooth from middle outward. Prick any bubbles remaining to the side gently with a straight pin. Push down with finders.

**To Remove:** Use a hairdryer. Continually heat as you pull evenly from top to bottom SLOWLY.

## **NOT RECOMMENDED:**

1: DO NOT apply to ceilings as gravity will pull it down.  
2: DO NOT apply to floors.

2: DO NOT use ANY cleaning products to clean wall-**especially any with Melaleuca Oil** in. IF necessary, use a small amt. of dish soap in water. Dry completely.

3: ANY uneven surfaces (concrete), etc.

**4: DO NOT apply to eggshell or flat latex paint.**

**\*\*We do not take responsibility of how and where decal is applied. Please follow these directions carefully. Options at our wall decal category for other types of mounting ideas at [www.allsportdesigns.com](http://www.allsportdesigns.com). Thank you.**

# Wall Decal Care Sheet

**Please Read Carefully!**

**ONLY apply this wall decal to GLOSS OR SEMI-GLOSS LATEX PAINTED WALLS**

**IF UNSURE (FOR ANY REASON) OF WHAT KIND OF PAINT IS ON YOUR WALL-\*DO NOT MOUNT!**

**\*See Optional Mounting Idea Below**

**Paint MUST be painted 30+ days PREVIOUSLY.**

1: Unroll and lay flat for 24 hrs. before application.

## **LOTION-FREE HANDS!!**

2: Apply decal straight down with both hands. If decal is large 2 people will be helpful. From middle outward, smooth decal with hands pushing air out from middle. Roll up a hand towel tightly and smooth from middle outward again. If any bubbles remain, gently pin prick to side of trapped air and push outward with finger.

3: Window application acceptable (Gymnasiums). Ideal temperature 50 Degrees or higher. Do not clean with ammonia cleaning products.

**Optional Mounting Idea: Purchase "Bath Board" at your local Lowe's or Home Depot. This is used to line shower walls. It is already painted smooth and is recommended for wall decals. You can usually get it cut to size while you wait. You can move your decal from wall to wall and keep FOREVER!**

**Car Decals:** **Vehicle Mounting:** Thoroughly clean and completely remove wax! Completely dry and wipe with rubbing alcohol. Let dry. Align decal to level. Tape on opposite sides to position helpful. Gently pull decal away from liner 1/2 way down decal. Cut off backing paper. Smooth decal from middle outward with a credit-type card for a squeegee. Lift remaining decal up to release remaining backing paper. Smooth decal from middle down and outward. Roll a hand towel up tightly. Smooth from middle outward. Prick any bubbles remaining to the side gently with a straight pin. Push down with finders.

**To Remove:** Use a hairdryer. Continually heat as you pull evenly from top to bottom SLOWLY.

## **NOT RECOMMENDED:**

1: DO NOT apply to ceilings as gravity will pull it down.  
2: DO NOT apply to floors.

2: DO NOT use ANY cleaning products to clean wall-**especially any with Melaleuca Oil** in. IF necessary, use a small amt. of dish soap in water. Dry completely.

3: ANY uneven surfaces (concrete), etc.

**4: DO NOT apply to eggshell or flat latex paint.**

**\*\*We do not take responsibility of how and where decal is applied. Please follow these directions carefully. Options at our wall decal category for other types of mounting ideas at [www.allsportdesigns.com](http://www.allsportdesigns.com). Thank you.**